

CHERRY Rockers

Series Name	Panel Cut-Out Approx Inches (mm)	Max UL Current Rating	Style		Approvals					Circuitry				Switch Function					Terminals					Actuator		
			Rocker	Pushbutton	UL	CSA	cULus	VDE	Lighted	SPST	SPDT	DPST	DPDT	On-Off	On-On	(On)-Off	(On) - On	On-Off-On	0.187" QC	0.250" QC	PCB Straight	PCB Left Angle	PCB Right Angle	Solder	Wire Leads	Flat
CR	1.12 (28.45) x 3 widths	20A 125VAC	✓		✓	✓		✓	✓	✓		✓	✓			✓		✓				✓		✓	✓	✓
SRB	0.760 x 0.508 (19.3 x 12.9)	10A 125VAC	✓		✓	✓		✓		✓	✓	✓	✓				✓	✓	✓	✓	✓	✓			✓	
SRJ	∅ 0.827 (21.00)	20A 125VAC	✓		✓		✓	✓		✓	✓	✓	✓				✓	✓	✓	✓	✓	✓			✓	
LR	0.760 x 0.508 (19.3 x 12.9)	10A 125VAC	✓		✓	✓		✓	✓		✓		✓		✓			✓	✓	✓					✓	
TR	1.20 x 0.433 (30.4 x 11.0)	16A 125VAC	✓		✓	✓		✓	✓		✓	✓	✓	✓			✓									✓
WR	1.19 x 0.867 (30.2 x 22.0)	16A 125VAC	✓		✓		✓	✓	✓		✓	✓	✓	✓			✓	✓				✓		✓	✓	✓
YR	1.19 x 0.867 (30.2 x 22.0)	20A 125VAC	✓		✓		✓	✓	✓		✓	✓	✓	✓			✓	✓				✓		✓	✓	✓
GR	1.13 x 0.535 (28.70 x 13.59)	15A 125VAC	✓		✓	✓		✓		✓	✓	✓	✓				✓					✓			✓	
RR	∅ 0.787 (20.0)	10A 125VAC	✓		✓	✓		✓	✓		✓						✓	✓		✓					✓	
PR	0.539 x 0.562 (13.7 x 9.2)	3A 250VAC	✓		✓		✓	✓		✓												✓		✓		
FR	0.752 x 0.862 (19.15 x 21.90)	12A 125VAC	✓		✓		✓	✓		✓	✓	✓	✓				✓					✓		✓		



FR



PR



RR



CR



SRB



SRJ



LR



TR



WR



YR



GR

02-08-12